(VITOPAN) STEELCLEAN S540

Page: 1

Compilation date: 28.03.17

Revision date: 16.05.18

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (VITOPAN) STEELCLEAN S540

Product code: S540

Synonyms: HC1553

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: KLEEN-TEX INDUSTRIES LTD

Unit 717 Eddington Way Birchwood Park Warrington WA3 6BA

United Kingdom

Tel: 01204 705070

Fax: 01204 861016

Email: info@kleen-tex.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)777 342 9963

Section 2: Hazards identification

2.1. Classification of the substance or mixture

 Classification under CLP: Asp. Tox. 1: H304; -: EUH066; -: EUH208
Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Contains citrus terpene blend. May produce an allergic reaction. May be fatal if swallowed and enters airways.

2.2. Label elements

| Label elements: | |
|--------------------|--|
| Hazard statements: | EUH066: Repeated exposure may cause skin dryness or cracking. |
| | EUH208: Contains citrus terpene blend. May produce an allergic reaction. |
| | H304: May be fatal if swallowed and enters airways. |
| Hazard pictograms: | GHS08: Health hazard |
| | |



(VITOPAN) STEELCLEAN S540

Signal words:DangerPrecautionary statements:P102: Keep out of reach of children.P260: Do not breathe spray.P260: Do not breathe spray.P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for
breathing.P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, LOW AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|-----|-----------|------------------------------|---------|
| 926-141-6 | - | - | Asp. Tox. 1: H304; -: EUH066 | 50-70% |

CITRUS TERPENE BLEND - REACH registered number(s): 01-2119493353-35

| 227-813-5 | 5989-27-5 | - | Flam. Liq. 3: H226; Skin Irrit. 2: H315; | <1% |
|-----------|-----------|---|--|-----|
| | | | Asp. Tox. 1: H304; Aquatic Chronic 1: | |
| | | | H410; Skin Sens. 1: H317 | |

Non-classified ingredients:

WHITE MINERAL OIL

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|-----------|-----------|--------------------|---------|
| 232-455-8 | 8042-47-5 | - | - | 30-50% |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

- **Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
- **Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

(VITOPAN) STEELCLEAN S540

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid. Spillage will create slippery surface.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

(VITOPAN) STEELCLEAN S540

Page: 4

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, LOW AROMATICS

| Workplace exposure limits: | | | Respirable dust | |
|----------------------------|-------------|--------------|-----------------|--------------|
| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| UK | 1200 mg/cm3 | - | - | - |

CITRUS TERPENE BLEND

| UK | 100ppm | 150ppm | - | - |
|----|--------|--------|---|---|
| | | | | |

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| State: | Liquid | | |
|-------------------------------|-------------|------------------------------|--------------------|
| Colour: | Blue | | |
| Odour: | Paraffinic | | |
| Evaporation rate: | Moderate | | |
| Solubility in water: | Insoluble | | |
| Viscosity: | Non-viscous | | |
| Boiling point/range°C: | 190 - 280 | Melting point/range°C: | No data available. |
| Flammability limits %: lower: | 0.5 | upper: | 6.0 |
| Flash point°C: | 70 | Part.coeff. n-octanol/water: | No data available. |
| Autoflammability°C: | >200 | Vapour pressure: | No data available. |
| Relative density: | 0.820 | pH: | Not applicable. |
| VOC g/l: | 650 | | |

9.2. Other information

Other information: No data available.

(VITOPAN) STEELCLEAN S540

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, LOW AROMATICS

| DERMAL | RBT | LD50 | >5000 | mg/kg |
|---------|-----|---------|-------|-------|
| ORAL | RAT | LD50 | >5000 | mg/kg |
| VAPOURS | RAT | 4H LC50 | >5000 | mg/kg |

CITRUS TERPENE BLEND

| ORL | RAT | LD50 | >4400 | mg/kg |
|-----|-----|------|-------|-------|
| SKN | RBT | LD50 | >2000 | mg/kg |

Non-classified ingredients:

WHITE MINERAL OIL

| DERMAL | RAT | LD50 | >2000 | mg/kg |
|--------|-----|------|-------|-------|
| ORAL | RAT | LD50 | >5000 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------|-------|-----------------------|
| Aspiration hazard | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

(VITOPAN) STEELCLEAN S540

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, LOW AROMATICS

| Daphnia magna | 48H EC50 | >250 | mg/l |
|-------------------------------------|----------|-------|------|
| RAINBOW TROUT (Oncorhynchus mykiss) | 96H LC50 | >1000 | mg/l |

CITRUS TERPENE BLEND

| FISH | 96H LC50 | 33 | mg/l |
|------|----------|----|------|
|------|----------|----|------|

WHITE MINERAL OIL

| RAINBOW TROUT (Oncorhynchus mykiss) | 96H LC50 | >400,000 | mg/l |
|-------------------------------------|----------|----------|------|
|-------------------------------------|----------|----------|------|

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier

than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

| 13.1. Waste treatment methods | | | |
|-------------------------------|---|--|--|
| Disposal operations: | Transfer to a suitable container and arrange for collection by specialised disposal | | |
| | company. | | |
| Recovery operations: | Solvent reclamation/regeneration. | | |
| Waste code number: | 20 01 13 | | |
| Disposal of packaging: | Dispose of as normal industrial waste. Clean with water. | | |
| NB: | The user's attention is drawn to the possible existence of regional or national | | |
| | regulations regarding disposal. | | |

(VITOPAN) STEELCLEAN S540

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. Reason for last issue number change-reviewed for correctness. IMPORTANT NOTE: Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product. See sections 2 and 3 for the calculated hazard and risk phrases for the blended product. Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains <name of sensitising substance>. May produce an allergic reaction. H226: Flammable liquid and vapour. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H410: Very toxic to aquatic life with long lasting effects. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. For professional and industrial use only.