H006: Selscale

concrete cleaner and descaler

Description of product

Removes cement and plaster splashes - ideal for initial cleaning. Cleans and etches concrete floors, ensures effective 'key' for seal application. Removes industrial grime and stains from brick and stone exterior. Descales and derusts metals prior to painting.

Product Uses

For cleaning and descaling brick, stone and concrete, quarry tiles etc. and for metal derusting.

Directions

Initial cleaning and concrete etching: Dilute SELSCALE 1 part to 4 parts water. Brush or spray. Allow to penetrate 5 to 10 minutes then rinse. For stubborn deposits use neat. Descaling metal: Dilute SELSCALE 1 part to 4 parts water. Brush on. Allow to descale, rinse, allow to dry. Paint or protect from corrosion immediately. N.B. 1. Do not use on or near linoleum floors, terrazzo, marble, acid sensitive stone, stainless steel, chrome or enamel. 2. Regular use on concrete will cause deterioration and is NOT recommended. 3. Descaled metal should be painted immediately to prevent rusting.

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit http://www.selden.co.uk/insight





typical dilution

Product Hazards and PPE Requirements

Danger

Risk Phrases

Causes severe skin burns and eye damage. Harmful if inhaled

Safety Phrases

Keep out of reach of children. Do not breathe spray. Avoid breathing spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective gloves, protective clothing. IF SWALLOWED: rinse mouth. Do NOT induce vomiting, IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention. Store locked up.

Technical Data

Composition An aqueous blend of hydrochloric acid, nonionic surface active agents, a rust inhibitor and dye

Appearance Clear thin liquid

Colour Red Density 1.10 рН Fragrance

Stability Two years minimum in unopened containers

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 -2004/648/EC. This requires all surfactants to break down both • If it can be recycled, it will be recycled. quickly and completely into harmless material such as CO2 . Our chemicals policy exceeds regulatory requirements.

Selden Environmental Charter

- . We set ourselves industryleading standards.
- · Selden minimises wastage, packaging and transportation.
- . We don't expect other people to clean up after us.
- . Conserving energy, preserving resources.
- . By being innovative, we strive to do better.
- . We like to work in partnership with our clients.
- Visit our website for more information

External Accreditations

9001 - Quality System

14001 - Environmental System 18001 - Health & Safety System IPPC Certified Manufacturer

Sustainability Product conforms with the

DEFRA endorsed Sustainable Cleaning quidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance. MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.

Selden Research Limited

Staden Business Park, Staden Lane, Buxton

Derbyshire, SK17 9RZ

Tel: 01298 26226 | Fax: 01298 26540 | Email: info@selden.co.uk | web: www.selden.co.uk













accredited testing laboratory No. 4204



SELDEN formulating testing manufacturing

the highest standards